#### **B-SIDE LED**

# Worktitude for light

#### BS1RD2510840NA



#### B-SIDE 360° LED 250 1000 NW ANT.

#### Description:

Bollard model B-SIDE 360° LED 250 1000, LAMP brand. Made in extruded recycled aluminum with a rate of 80% and injection, and translucent polycarbonate diffuser. 250mm in height. Its base has an anti-corrosion electro coating treatment. Model for COB LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 50.000 L90 B10. Available finishes: anthracite and textured grey.



Finish: Textured anthracite

Dimensions: Ø 160 mm x 250 mm Weight: 3.620 g

Installation: Standing

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 423 lm
 °K:
 4000

 Plum:
 10,1W
 CRI:
 80

 Efficacy:
 41,8 lm/w
 MacAdam:
 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 8W

#### Light output tolerance +/- 10%





















# CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















## **B-SIDE LED**








#### **PHOTOMETRIC DATA:**

 $_{\eta}$  = 100% | Imax = 251 cd/klm | UTE: 0,86I + 0,15T | CIE: 24 67 92 86 100



#### **Product datasheet**

## **B-SIDE LED**



ACCESORIES:

Optical



Product code: Description:

BSSC180B B-SIDE ACC. 180° SCREEN 56MM