B-SIDE LED


BS1RD8525840NG



B-SIDE 360° LED 850 2500 NW GR.

Description:

Bollard model B-SIDE 360° LED 850 2500, LAMP brand. Made in extruded recycled aluminum with a rate of 80% and injection, and translucent polycarbonate diffuser. 850mm in height. Its base has an anti-corrosion electro coating treatment. Model for COB LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 50.000 L70 B10. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Dimensions: Ø 160 mm x 850 mm Weight: 4.384 g

Installation: Standing

TECHNICAL SPECIFICATIONS:

Light output: 805 lm °K: 4000 Plum: 19,2W CRI: 80 Efficacy: 41,9 lm/w 3 MacAdam:

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

17W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:

























B-SIDE LED




B-SIDE 360° LED 850 2500 NW GR.



PHOTOMETRIC DATA:

5841313 $_{\eta}$ = 100% $_{Imax}$ = 253 cd/klm $_{UTE}$: 0,86I + 0,14T $_{CIE}$: 24 67 92 86 100



Product datasheet

B-SIDE LED



ACCESORIES:

Optical



Product code: Description:

BSSC180B B-SIDE ACC. 180° SCREEN 56MM