B-SIDE LED

BS2182510830NG



B-SIDE G2 180º 250 1200 WW GR

Description:

Bollard model B-SIDE G2 180º LED 250 1200, LAMP brand. Made of lacquered aluminium injection, and translucent polycarbonate diffuser. 250mm height. Its base has an anti-corrosion electro coating treatment. 3000K CRI 80 LED. Control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 72. 000 L80 B10. BUG Rate: B0 U2 G1, ULOR: 7,4%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Dimensions: Ø 160 mm x 450 mm Weight: 3.620 g

Installation: Standing

TECHNICAL SPECIFICATIONS:

Light output: 350 lm °K: 3000 Plum: 8,7W CRI: 80 Efficacy: 40,2 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

6,5W Power:

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















B-SIDE LED



B-SIDE G2 180º 250 1200 WW GR



PHOTOMETRIC DATA:

BS2182510830NG η = 100% lmax = 502 cd/klm UTE: 0,08T CIE: 12 47 82 92 100





