B-SIDE LED


BS2188510840NG



B-SIDE G2 180º 850 1200 NW GR

Description:

Bollard model B-SIDE G2 180º LED 850 1200, LAMP brand. Manufactured from die-cast aluminium and extruded body of recycled aluminium with an 80% lacquered rate and translucent diffuser. 850mm height. Its base has an anti-corrosion electro coating treatment. 4000K CRI 80 LED. Control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 72. 000 L80 B10. BUG Rate: B0 U2 G1, ULOR: 7,4%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Dimensions: Ø 160 mm x 850 mm Weight: 4.384 g

Installation: Standing

TECHNICAL SPECIFICATIONS:

Light output: 370 lm °K: 4000 Plum: 8,7W CRI: 80 Efficacy: 42,5 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

6,5W Power:

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















B-SIDE LED



BS2188510840NG

B-SIDE G2 180º 850 1200 NW GR

PHOTOMETRIC DATA:

BS2188510840NG η = 100% lmax = 502 cd/klm UTE: 0,08T CIE: 12 47 82 92 100

