Product datasheet

B-SIDE LED

Worktitude for light

BS2362510830NG



B-SIDE G2 360° 250 1200 WW GR

Description:

Bollard model B-SIDE G2 360° LED 250 1200, LAMP brand. Made of lacquered aluminium injection, and translucent polycarbonate diffuser. 250mm height. Its base has an anti-corrosion electro coating treatment. 3000K CRI 80 LED. Control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 72. 000 L80 B10. BUG Rate: B0 U2 G1, ULOR: 3,5%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Dimensions: Ø 160 mm x 450 mm Weight: 3.620 g

Installation: Standing

TECHNICAL SPECIFICATIONS:

 Light output:
 530 lm
 °K:
 3000

 Plum:
 8,7W
 CRI:
 80

 Efficacy:
 60,9 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 6,5W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















B-SIDE LED



BS2362510830NG

B-SIDE G2 360° 250 1200 WW GR

PHOTOMETRIC DATA:

BS2362510830NG η = 100% lmax = 267 cd/klm UTE: 0,04T CIE: 12 50 86 96 100





