Product datasheet

DOMO 220




DO2RD20AS830DW



DOMO 220 G2 ASYM 2000 WW DALI

Description:

Round recessed DOMO 220 G2 ASYM 2000 downlight, LAMP brand. With external ring in white lacquered diecast aluminium and with polycarbonate opal diffuser. Model for MID-POWER LED, 3000K colour temperature and control gear included. Lower asymmetric reflector in high purity aluminium. Insulation class II. Lifetime: 50.000 L90



Finish: Matte white RAL 9010

Weight: 1.538 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.534 lm °K: 3000 Plum: 23W CRI: 80 Efficacy: 66,7 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 120-240V 50/60Hz LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Adjustable DALI

21W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















DOMO 220




DOMO 220 G2 ASYM 2000 WW DALI



PHOTOMETRIC DATA:

10041130 η = 100% Imax = 582 cd/klm UTE: 1,00C + 0,00T CIE: 65 93 99 100 100



DOMO 220



ACCESORIES:

Optical



Product code:

Description:

DITRRD240B DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

DITRRD240G DOMO 220/KOMBIC ACC.TRANSP GLASS GR. DITRRD240W DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

RIRD240G RIRD240W Description:

DOMO 220/KOMBIC ACC. DECO RING GR. DOMO 220/KOMBIC ACC. DECO RING WH.