Product datasheet

DOMO 220

160 150

DO2RD20AS830NW



ø 220 mm

DOMO 220 G2 ASYM 2000 WW

Description:

Round recessed DOMO 220 G2 ASYM 2000 downlight, LAMP brand. With external ring in white lacquered diecast aluminium. Model for MID-POWER LED, 3000K colour temperature and control gear included. Lower asymmetric reflector in high purity aluminium and with polycarbonate opal diffuser. Insulation class II. Lifetime: 50.000 L90 B10

Finish: Matte white RAL 9010

Weight: 1.538 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.534 lm	°К :	3000
Plum:	23W	CRI :	80
Efficacy:	66,7 lm/w	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	120-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	21W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light


DOMO 220

10041130 η = 100%

DO2RD20AS830NW

DOMO 220 G2 ASYM 2000 WW







Product datasheet

DOMO 220

ACCESORIES :

Optical



Product code: DITRRD240B Description: DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code: DITRRD240G DITRRD240W Description: DOMO 220/KOMBIC ACC.TRANSP GLASS GR. DOMO 220/KOMBIC ACC.TRANSP GLASS WH.

Worktitude for light



Product code: RIRD240B Description: DOMO 220/KOMBIC ACC. DECO RING BK.



Product code: RIRD240G RIRD240W Description: DOMO 220/KOMBIC ACC. DECO RING GR.

DOMO 220/KOMBIC ACC. DECO RING WH.