Product datasheet

DOMO 220




DO2RD40SY840NW



DOMO 220 G2 4000 NW

Description:

Round recessed DOMO 220 G2 4000 downlight, LAMP brand. With external ring in white lacquered die-cast aluminium. Model for MID-POWER LED, 4000K colour temperature and control gear included. Reflector designed by the optical concept named REDIL® (Direct Emission LED Reflector), which consists of a two-phase reflection. Insulation class II. Lifetime: 50.000 L80 B10



Finish: Matte white RAL 9010

Weight: 1.508 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.812 lm °K: 4000 Plum: 40,5W CRI: 80 Efficacy: 94,1 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 120-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

37W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:
























DOMO 220





DO2RD40SY840NW

DOMO 220 G2 4000 NW

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,40	2924	1692
2	2,80	731	423
3	4,20	325	188
4	5,59	183	106

DOMO 220



ACCESORIES:

Optical



Product code:

8606130

Description:

DOMO 220 G2 ACC. INT OPAL DIFFUSER



Product code:

DIOPRD240W

Description: DIOPRD240G DOMO 220 ACC. OPAL GLASS GR.

DOMO 220 ACC. OPAL GLASS WH.



Product code:

Description:

DITRRD240B DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

DITRRD240G DITRRD240W DOMO 220/KOMBIC ACC.TRANSP GLASS GR. DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

RIRD240G DOMO 220/KOMBIC ACC. DECO RING GR. RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.

Data according to regulations 2019/2020/EU and 2019/2015/EU

DOMO 220



