#### **Product datasheet**

#### **DOMO SPOTLIGHT**



#### **DP214FL830NW**



#### **DOMO 160 SPOT G2 1500 WW FL WH.**

#### Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 1500 WW FL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with warm white colour temperature and control gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 758 g



Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.168 lm °K: 3000 Plum: 9,9W CRI: 80 Efficacy: 117,9 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

9W Power:

### Light output tolerance +/- 10%



























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















# **DOMO SPOTLIGHT**



**DP214FL830NW** 

# **DOMO 160 SPOT G2 1500 WW FL WH.**

### **PHOTOMETRIC DATA:**

DP214FL830NW  $\eta$  = 100% lmax = 2773 cd/klm UTE: CIE: 99 100 100 100 100



