DOMO SPOTLIGHT

LAMP Worktitude for light


DP214FL840DW



DOMO 160 SPOT G2 1500 NW FL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 1500 NW FL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

 Light output:
 1.217 lm
 °K:
 4000

 Plum:
 9.9W
 CRI:
 80

 Efficacy:
 122,8 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L90 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 9W

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:



























DOMO SPOTLIGHT




DP214FL840DW

DOMO 160 SPOT G2 1500 NW FL DALI WH.

PHOTOMETRIC DATA:

DP214FL840NW η = 100% lmax = 2773 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 29,9°	H (m)	D (m)	Emax	Emed
\wedge	1	0,53	3360	2262
	2	1,07	840	565
	3	1,60	373	251
	4	2,14	210	141