#### **Product datasheet**

## **DOMO SPOTLIGHT**




## **DP214FL840NW**



## **DOMO 160 SPOT G2 1500 NW FL WH.**

## Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 1500 NW FL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.





Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 1.217 lm °K: 4000 Plum: 9,9W CRI: 80 Efficacy: 122,8 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

9W Power:

# Light output tolerance +/- 10%





























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















# **DOMO SPOTLIGHT**




**DP214FL840NW** 

# **DOMO 160 SPOT G2 1500 NW FL WH.**

# **PHOTOMETRIC DATA:**

DP214FL840NW  $_{\eta}$  = 100%  $_{Imax}$  = 2773 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 29,9°	H (m)	D (m)	Emax	Emed
$\wedge$	1	0,53	3360	2262
	2	1,07	840	565
	3	1,60	373	251
	4	2,14	210	141