Product datasheet

DOMO SPOTLIGHT




DP214MF840NW



DOMO 160 SPOT G2 1500 NW MFL WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 1500 NW MFL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

 Light output:
 1.257 lm
 %K:
 4000

 Plum:
 9,9W
 CRI:
 80

 Efficacy:
 126,9 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 9W

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT




DP214MF840NW

DOMO 160 SPOT G2 1500 NW MFL WH.

PHOTOMETRIC DATA:

DP214MF840NW η = 100% Imax = 3916 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 24,4°	H (m)	D (m)	Emax	Emed
\wedge	1	0,43	4909	3504
	2	0,86	1227	876
	3	1,30	545	389
	4	1,73	307	219