Product datasheet

DOMO SPOTLIGHT



DP225FL830NW




DOMO 160 SPOT G2 2500 WW FL WH.

Matte white RAL 9010

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 2500 WW FL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with warm white colour temperature and control gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Weight: 758 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.190 lm °K: 3000 Plum: 19,2W CRI: 80 Efficacy: 114 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

18W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















DOMO SPOTLIGHT




DP225FL830NW

DOMO 160 SPOT G2 2500 WW FL WH.

PHOTOMETRIC DATA:





alpha = 29,9°	H (m)	D (m)	Emax	Emed
\wedge	1	0,53	6048	4071
	2	1,07	1512	1018
	3	1,60	672	452
	4	2,14	378	254