Product datasheet

DOMO SPOTLIGHT



DP225FL840NW



DOMO 160 SPOT G2 2500 NW FL WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 2500 NW FL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.





Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.281 lm
 °K:
 4000

 Plum:
 19,2W
 CRI:
 80

 Efficacy:
 118,8 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT




DP225FL840NW

DOMO 160 SPOT G2 2500 NW FL WH.

PHOTOMETRIC DATA:

DP225FL840NW $_{\eta}$ = 100% $_{Imax}$ = 2773 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 29,9°	H (m)	D (m)	Emax	Emed
	1	0,53	6300	4241
	2	1,07	1575	1060
	3	1,60	700	471
	4	2,14	394	265

Data according to regulations 2019/2020/EU and 2019/2015/EU