DOMO SPOTLIGHT




DP225MF840DW



DOMO 160 SPOT G2 2500 NW MFL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 2500 NW MFL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.357 lm
 °K:
 4000

 Plum:
 19,2W
 CRI:
 80

 Efficacy:
 122,7 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 18W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT




DP225MF840DW

DOMO 160 SPOT G2 2500 NW MFL DALI WH.

PHOTOMETRIC DATA:

DP225MF840NW η = 100% lmax = 3916 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 24,4°	H (m)	D (m)	Emax	Emed
\wedge	1	0,43	9205	6569
	2	0,86	2301	1642
	3	1,30	1023	730
	4	1,73	575	411