Product datasheet

DOMO SPOTLIGHT



DP225MF840NW



DOMO 160 SPOT G2 2500 NW MFL WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 2500 NW MFL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.





Finish: Matte white RAL 9010

Weight: 758 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.357 lm °K: 4000 Plum: 19,2W CRI: 80 Efficacy: 122,7 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

18W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:

























DOMO SPOTLIGHT




DP225MF840NW

DOMO 160 SPOT G2 2500 NW MFL WH.

PHOTOMETRIC DATA:

DP225MF840NW $\eta = 100\%$ $Imax = 3916 \ cd/klm$ UTE: CIE: 99 100 100 100 100



alpha = 24,4°	H (m)	D (m)	Emax	Emed
\wedge	1	0,43	9205	6569
	2	0,86	2301	1642
	3	1,30	1023	730
	4	1,73	575	411