DOMO SPOTLIGHT

DP235FL830DW



DOMO 160 SPOT G2 3500 WW FL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 3500 WW FL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with warm white colour temperature and control DALI gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 808 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.004 Im °K: 3000 Plum: 31,4W CRI: 80 Efficacy: 95,6 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Adjustable DALI

28W Power:

Light output tolerance +/- 10%















IP

20













CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT




DP235FL830DW

DOMO 160 SPOT G2 3500 WW FL DALI WH.

PHOTOMETRIC DATA:

DP235FL830NW η = 100% lmax = 2773 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 29,9°	H (m)	D (m)	Emax	Emed
\wedge	1	0,53	8296	5584
	2	1,07	2074	1396
	3	1,60	922	620
	4	2,14	519	349