DOMO SPOTLIGHT




DP235FL840DW



DOMO 160 SPOT G2 3500 NW FL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 3500 NW FL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 808 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

Light output: 3.129 lm °K: 4000 Plum: 31,4W CRI: 80 Efficacy: 99,6 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Adjustable DALI

28W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT




DP235FL840DW

DOMO 160 SPOT G2 3500 NW FL DALI WH.

PHOTOMETRIC DATA:

DP235FL840NW $_{\eta}$ = 100% $_{Imax}$ = 2773 cd/klm UTE: CIE: 99 100 100 100 100



| alpha = 29,9° | H (m) | D (m) | Emax | Emed |
|---------------|-------|-------|------|------|
| \wedge | 1 | 0,53 | 8642 | 5817 |
| | 2 | 1,07 | 2161 | 1454 |
| | 3 | 1,60 | 960 | 646 |
| | 4 | 2,14 | 540 | 364 |