Product datasheet

DOMO SPOTLIGHT




DP235FL840NW



DOMO 160 SPOT G2 3500 NW FL WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 3500 NW FL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 808 g

2

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.129 lm
 °K:
 4000

 Plum:
 31,4W
 CRI:
 80

 Efficacy:
 99,6 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

Power: 28W

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















DOMO SPOTLIGHT



DP235FL840NW

DOMO 160 SPOT G2 3500 NW FL WH.

PHOTOMETRIC DATA:

DP235FL840NW η = 100% lmax = 2773 cd/klm UTE: CIE: 99 100 100 100 100

