DOMO SPOTLIGHT

Worktitude for light


DP235MF840DW



DOMO 160 SPOT G2 3500 NW MFL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 3500 NW MFL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 808 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.232 lm
 °K:
 4000

 Plum:
 31,4W
 CRI:
 80

 Efficacy:
 102,9 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 28W

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:




























DOMO SPOTLIGHT




DP235MF840DW

DOMO 160 SPOT G2 3500 NW MFL DALI WH.

PHOTOMETRIC DATA:





alpha = 24,4°	H (m)	D (m)	Emax	Emed
\wedge	1	0,43	12622	9008
	2	0,86	3156	2252
	3	1,30	1402	1001
	4	1,73	789	563