Product datasheet

DOMO SPOTLIGHT



DP235MF840NW



DOMO 160 SPOT G2 3500 NW MFL WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 3500 NW MFL WH., LAMP brand. Made of white lacquered injected aluminium. Passive dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.





Finish: Matte white RAL 9010

Weight: 808 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.232 lm °K: 4000 Plum: 31,4W CRI: 80 Efficacy: 102,9 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

28W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















DOMO SPOTLIGHT




DP235MF840NW

DOMO 160 SPOT G2 3500 NW MFL WH.

PHOTOMETRIC DATA:

DP235MF840NW $_{\eta}$ = 100% $_{lmax}$ = 3916 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 24,4°	H (m)	D (m)	Emax	Emed
\wedge	1	0,43	12622	9008
	2	0,86	3156	2252
	3	1,30	1402	1001
	4	1,73	789	563