DOMO SPOTLIGHT

Worktitude for light


DP246FL840DW



DOMO 160 SPOT G2 4600 NW FL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 4600 NW FL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Active dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 886 g

120 103

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 4.125 lm
 °K:
 4000

 Plum:
 36,2W
 CRI:
 80

 Efficacy:
 114 lm/w
 MacAdam:
 3

 Type:
 COB PHILIPS
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 33W

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU




















DOMO SPOTLIGHT




DP246FL840DW

DOMO 160 SPOT G2 4600 NW FL DALI WH.

PHOTOMETRIC DATA:





alpha = 32,6°	H (m)	D (m)	Emax	Emed
\wedge	1	0,58	10208	6891
	2	1,17	2552	1723
	3	1,75	1134	766
	4	2,34	638	431

Data according to regulations 2019/2020/EU and 2019/2015/EU