DOMO SPOTLIGHT



DP246MF830DW



DOMO 160 SPOT G2 4600 WW MFL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 4600 WW MFL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Active dissipation for a proper thermal management. Model for COB LED, with warm white colour temperature and control DALI gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 886 g

Installation: Recessed



Light output: 3.859 lm °K: 3000 Plum: 36,2W CRI: 80 Efficacy: 106,6 lm/w 3 MacAdam:

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

33W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU




















DOMO SPOTLIGHT




DP246MF830DW

DOMO 160 SPOT G2 4600 WW MFL DALI WH.

PHOTOMETRIC DATA:





alpha = 23,2°	H (m)	D (m)	Emax	Emed
\wedge	1	0,41	15115	10580
	2	0,82	3779	2645
	3	1,23	1679	1176
	4	1,64	945	661