DOMO SPOTLIGHT




DP246MF840DW



DOMO 160 SPOT G2 4600 NW MFL DALI WH.

Description:

Adjustable recessed downlight model DOMO 160 SPOT G2 4600 NW MFL DALI WH., LAMP brand. Made of white lacquered injected aluminium. Active dissipation for a proper thermal management. Model for COB LED, with neutral white colour temperature and control DALI gear included. With aluminium reflector of Medium Flood optic. Insulation class II. It allows swivels between -30° and 30°.



Finish: Matte white RAL 9010

Weight: 886 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 4.020 lm
 °K:
 4000

 Plum:
 36,2W
 CRI:
 80

 Efficacy:
 111 lm/w
 MacAdam:
 3

 Type:
 COB PHILIPS
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 33W

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:

























DOMO SPOTLIGHT




DP246MF840DW

DOMO 160 SPOT G2 4600 NW MFL DALI WH.

PHOTOMETRIC DATA:

DP246MF840NW η = 100% lmax = 3930 cd/klm UTE: CIE: 99 100 100 100 100



| alpha = 23,2° | H (m) | D (m) | Emax | Emed |
|---------------|-------|-------|-------|-------|
| \wedge | 1 | 0,41 | 15745 | 11021 |
| | 2 | 0,82 | 3936 | 2755 |
| | 3 | 1,23 | 1749 | 1225 |
| | 4 | 1,64 | 984 | 689 |