Product datasheet

FIL35



F31RE084MOOC840NW



- FIL35 REC 840 2220 NW OP COMF WH.

Description:

Finish: Matte white RAL 9010

Installation: Recessed



TECHNICAL SPECIFICATIONS:

 Light output:
 1.223 lm
 ⁰K :
 4000

 Plum:
 13,5W
 CRI :
 80

 Efficacy:
 90,6 lm/w
 MacAdam:
 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

UGR: <19

Type: MID POWER LED

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 12W


Light output tolerance +/- 10%

EPD

Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL35











PHOTOMETRIC DATA:

F31RE084MOOC840NW η = 99% Imax = 693 cd/klm UTE: 0,99C









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW Description:

FIL 35 ACC. COVER X/MM WH.