## **Product datasheet**

## FIL35




## F31RE112MOOC840NW



## - FIL35 REC 1120 2960 NW OP COMF WH.

#### Description:



Finish: Matte white RAL 9010

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.630 lm
 %:
 4000

 Plum:
 18W
 CRI:
 80

 Efficacy:
 90,6 lm/w
 MacAdam:
 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

**UGR**: <19

Type: MID POWER LED

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)

Power: 16W

Light output tolerance +/- 10%

EPD

Data according to regulations 2019/2020/EU and 2019/2015/EU


## FIL35








#### **PHOTOMETRIC DATA:**

F31RE112MOOC840NW η = 99% Imax = 693 cd/klm UTE: 0,99C









## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW Description:

FIL 35 ACC. COVER X/MM WH.