FIL35


F31RE112MOTE940NW

FIL35 REC 1120 2960 9NW TECH WH



Description:

Recessed structure for suspension or surface mounting, model FIL35 TECH by LAMP. Made of 80% recycled aluminium extrusion, length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<12. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP43, IK07 degree of protection. Insulation class I. Photobiological safety group 0. Lifetime: 50000 L90 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010 Dimensions: 1.120 x 35 x 76 mm

Weight: 3.240 g

Installation: Recessed

1,128 x 42 x 0 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 1.760 lm °K: 4000 Plum: 17,8W CRI: 90 Efficacy: 98,9 lm/w R9: 85 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

14W Power:

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















F31RE112MOTE940NW



FIL35 REC 1120 2960 9NW TECH WH

PHOTOMETRIC DATA:

F31RE112MOTE940NW η = 100% Imax = 1333 cd/klm UTE:

CIE: 98 100 100 100 100

