## **Product datasheet**

## FIL35



## F31RE168MOOC830NW

# FIL35 REC 1680 4440 WW OP COMF WH.



Description:

76

Finish: Matte white RAL 9010

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.357 lm
 ⁰K :
 3000

 Plum:
 25,2W
 CRI :
 80

 Efficacy:
 93,5 lm/w
 MacAdam:
 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

**UGR:** <19

Type: MID POWER LED

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)

Power: 22W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es

## FIL35








FIL35 REC 1680 4440 WW OP COMF WH.


#### **PHOTOMETRIC DATA:**

F31RE168MOOC830NW  $\eta$  = 99% lmax = 693 cd/klm UTE: 0,99C









## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW Description:

FIL 35 ACC. COVER X/MM WH.