Product datasheet

FIL35




F31RE168MOOP840DW



- FIL35 REC 1680 4440 NW OPAL DALI WH.

Description:



Finish: Matte white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.658 lm
 % :
 4000

 Plum:
 25,2W
 CRI :
 80

 Efficacy:
 105,5 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI


Power: 22W

Light output tolerance +/- 10%

EPD

FIL35










PHOTOMETRIC DATA:


$$\label{eq:eta-problem} \begin{split} &\text{F31RE168MOOP840DW} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW Description:

FIL 35 ACC. COVER X/MM WH.