Product datasheet

FIL35



F31RE224LOOC830NB



FIL35 REC 2240 3200 WW OP COMF BK.

Description:

Structure to recessed model FIL35 REC 2240 3200 WW OPAL COMF BK., LAMP brand. Made of extruded aluminium painted in matt black with and opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, warm white color temperature and control gear included. With IP20, IK07 protection rating. Insulation class I. Photobiological safety group 0.

Finish: Matte black RAL 9011

Dimensions: 2.240 x 45 x 76 mm

Installation: Recessed

Recessing measures: 2,248 x 42 x 0 mm

TECHNICAL SPECIFICATIONS:

°K: 3000

 UGR:
 19
 CRI:
 80

 Type:
 MID POWER TRIDONIC
 MacAdam:
 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Gear: Electronic

CUSTOM MADE OPTIONS:

























FIL35





FIL35 REC 2240 3200 WW OP COMF BK.




PHOTOMETRIC DATA:

F31RE224LOOC830NB η = 99% Imax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99







FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code:

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3REECB

Description:

FIL 35 ACC. REC END COVER BK.



Product code:

F3REECG

Description:

FIL 35 ACC. REC END COVER GR.



Product code:

F3REECW

Description:

FIL 35 ACC. REC END COVER WH.