Product datasheet

FIL35

F31RE224LOOP830DG



FIL35 REC 2240 3200 WW OPAL DALI GR.

Description:

Structure to recessed model FIL35 REC 2240 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring Dali included. With IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED lifetime: 50.000 L90 B10. Available finishes: White, black and grey.



Finish: Gloss grey

Dimensions: 2.240 x 45 x 76 mm Weight: 5.350 g

Installation: Recessed

Recessing measures: 2,248 x 42 x 0 mm

TECHNICAL SPECIFICATIONS:

Light output: 2.310 lm °K: 3000 Plum: 21,7W CRI: 80 Efficacy: 106,5 lm/w MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Adjustable DALI

21W Power:

Light output tolerance +/- 10%































CUSTOM MADE OPTIONS:






























F31RE224LOOP830DG








PHOTOMETRIC DATA:


F31RE224LOOP830NG η = 100% Imax = 395 cd/klm UTE: 1,00E

CIE: 50 81 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code:

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3PRREX/MMB

Description:

FIL 35 ACC. REC PROFIL X/MM BK.



Product code:

F3PRREX/MMG

Description:

FIL 35 ACC. REC PROFIL X/MM GR.



Product code:

F3PRREX/MMW

Description:

FIL 35 ACC. REC PROFIL X/MM WH.



Product code:

F3REECB

Description:

FIL 35 ACC. REC END COVER BK.



Product code:

F3REECG

Description:

FIL 35 ACC. REC END COVER GR.



Product code:

F3REECW

Description:

FIL 35 ACC. REC END COVER WH.



Product code:

F3REJO

Description:

FIL35 ACC. INTM JOINT B RECESSED

ACCESORIES:

Optical

Product datasheet

FIL35





Product code:

Description:

F3DIX/MMOP

FIL 35 ACC. OPAL DIFFUSER X/MM