FIL35



F31SF112MOOP830NB

- FIL35 SUR 1120 2960 WW OPAL BK.

Description:

Finish: Matte black RAL 9011

80

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.708 lm
 ⁰K :
 3000

 Plum:
 18W
 CRI :
 80

 Efficacy:
 94,9 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Gear:

Electronic

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 16W

Light output tolerance +/- 10%

EPD

CUSTOM MADE OPTIONS:



FIL35



FIL35 SUR 1120 2960 WW OPAL BK.





PHOTOMETRIC DATA:


$$\label{eq:eta-problem} \begin{split} &\text{F31SF112MOOP830NB} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.