FIL35

F31SF140LOIO830NB FIL35 SUR 1400 3800 WW D/I OPAL BK.



Description:

Suspended structure model FIL35 SUR 1400 D/I LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring included. With IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED lifetime: 50.000 L90 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte black RAL 9011 Dimensions: 1.400 x 35 x 80 mm

Weight: 3.170 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.817 lm °K: 3000 Plum: 27,4W CRI: 80 Efficacy: 102,8 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 23W

Light output tolerance +/- 10%



CLASE























CUSTOM MADE OPTIONS:




























FIL35





FIL35 SUR 1400 3800 WW D/I OPAL BK.




PHOTOMETRIC DATA:









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.



Product code:

F3JO

Description:

FIL35 ACC. INTM JOINT B



Product code:

F3PRSUX/MMB

Description:

FIL 35 ACC. SUS PROFIL X/MM BK.



Product code:

F3PRSUX/MMG

Description:FIL 35 ACC. SUS PROFIL X/MM GR.



Product code:

F3PRSUX/MMW

Description:

FIL 35 ACC. SUS PROFIL X/MM WH.

Product datasheet

FIL35





Product code:

F3SUECB



FIL35 ACC. SUR END COVER BK.



Product code:

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.



Product code:

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

ACCESORIES:

Suspension



Product code:

F3SUCAEMFA1000NB F3SUCAEMFA4000NB



ACC. ELECMEC FIL35 QUICK SUSP 1M BK. ACC. ELECMEC FIL35 QUICK SUSP 4M BK.



Product code:

F3SUCAEMFA1000NG F3SUCAEMFA4000NG



ACC. ELECMEC FIL35 QUICK SUSP 1M GR. ACC. ELECMEC FIL35 QUICK SUSP 4M GR.



Product code:

F3SUCAEMFA1000NW F3SUCAEMFA4000NW

Description:

ACC. ELECMEC FIL35 QUICK SUSP 1M WH. ACC. ELECMEC FIL35 QUICK SUSP 4M WH.



Product code:

F3SUCAWI1000DB F3SUCAWI4000DB

Description:

ACC. ELECMEC FIL35 QUICK SUSP 1M 5P BK. ACC. ELECMEC FIL35 QUICK SUSP 4M 5P BK.



Product code:

F3SUCAWI1000DG F3SUCAWI4000DG

Description:

ACC. ELECMEC FIL35 QUICK SUSP 1M 5P GR. ACC. ELECMEC FIL35 QUICK SUSP 4M 5P GR.



Product code:

F3SUCAWI1000DW F3SUCAWI4000DW

Description:

ACC. ELECMEC FIL35 QUICK SUSP 1M 5P WH. ACC. ELECMEC FIL35 QUICK SUSP 4M 5P WH.

Product datasheet

FIL35





Product code: F3SUWIDE1000G

Description:

FIL35 ACC. QUICK STEEL CABLE 1M NK.



Product code:

F3SUWIDE4000G

Description:

FIL35 ACC. QUICK STEEL CABLE 4M NK.

ACCESORIES:

Support



Product code:

Description:

F3FX15G

ACC. CEILING BRACKET FIL35 15MM GR.

ACCESORIES:

Optical



Product code:

Description:

F3DIX/MMOP

FIL 35 ACC. OPAL DIFFUSER X/MM