Product datasheet

FIL35



F31SF140MOOC830NB

FIL35 SUR 1400 3700 WW OP COMF BK.



Description:

Matte black RAL 9011 Finish:

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.964 lm °K: 3000 21,2W Plum: CRI: 80 Efficacy: 92,7 lm/w MacAdam: 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

UGR: <19

Type: MID POWER LED

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 19W

Light output tolerance +/- 10%

EPD

CUSTOM MADE OPTIONS:



Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL35








FIL35 SUR 1400 3700 WW OP COMF BK.

PHOTOMETRIC DATA:

F31SF140MOOC830NB η = 99% lmax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99







Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.