## **Product datasheet**

## FIL35



## F31SF140MOOC840NB

- FIL35 SUR 1400 3700 NW OP COMF BK.



Description:



Finish: Matte black RAL 9011

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.038 lm
 %:
 4000

 Plum:
 21,2W
 CRI:
 80

 Efficacy:
 96,1 lm/w
 MacAdam:
 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

**UGR:** <19

Type: MID POWER LED

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)

Power: 19W

Light output tolerance +/- 10%

EPD

## FIL35











#### **PHOTOMETRIC DATA:**

F31SF140MOOC840NB η = 99% Imax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99









#### **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# ACCESORIES:

# Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.