


F31SF196LOIC830DB


**FIL35 SUR 1960 5400 WW D/I COMF DALI BK.****Description:**

Suspended structure model FIL35 SUR 1960 5400 WW D/I OP COMF DALI BK. LAMP brand. Made of extruded aluminium painted in matt black. Indirect-direct light. With an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, warm white color temperature and control DALI gear included. With IP20, IK07 protection rating. Insulation class I. Photobiological safety group 0.

Finish: Matte black RAL 9011**Dimensions:** 1.960 x 35 x 80 mm**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

Light output:	3.750 lm	°K :	3000
Plum:	36,2W	CRI :	80
Efficacy:	102,8 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER TRIDONIC	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	32W		


Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

ACCESSORIES :
Assembly**Product code:**

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

**Product code:**

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.

**Product code:**

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.

**Product code:**

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.

**Product code:**

F3FX50G

Description:


ACC. WALL BRACKET FIL35 50MM GR.

**Product code:**

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

**Product code:**

F3SUECB

Description:

FIL35 ACC. SUR END COVER BK.

**Product code:**

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.

**Product code:**

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

ACCESSORIES :
Suspension

FIL35



Product code:
F3SUWIDE1000G

Description:
FIL35 ACC. QUICK STEEL CABLE 1M NK.



Product code:
F3SUWIDE4000G

Description:
FIL35 ACC. QUICK STEEL CABLE 4M NK.

ACCESORIES :
Support



Product code:
F3FX15G

Description:
ACC. CEILING BRACKET FIL35 15MM GR.