

F31SF196LOOC840DW



FIL35 SUR 1960 2800 NW OP COMF DALI WH.

Description:**Finish:** Matte white RAL 9010**Dimensions:** 1.960 x 35 x 80 mm**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	1.946 lm	°K :	4000
Plum:	18,9W	CRI :	80
Efficacy:	103 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER TRIDONIC	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	19W		

*Light output tolerance +/- 10%***CUSTOM MADE OPTIONS:**

ACCESORIES :

Assembly




Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.




Product code:

F3SUECB

Description:

FIL35 ACC. SUR END COVER BK.



Product code:

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.



Product code:

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

ACCESORIES :

Suspension



Product code:

F3SUWIDE1000G

Description:

FIL35 ACC. QUICK STEEL CABLE 1M NK.



Product code:

F3SUWIDE4000G

Description:

FIL35 ACC. QUICK STEEL CABLE 4M NK.