## **Product datasheet**

## FIL35



## F31SF196MOOP830NG



- FIL35 SUR 1960 5180 WW OPAL GR.

Description:

Finish: Gloss grey

80

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.989 lm
 %:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 106,8 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Gear:

Electronic

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)

Power: 25W

Light output tolerance +/- 10%

EPD

**CUSTOM MADE OPTIONS:** 

RAW

## FIL35



FIL35 SUR 1960 5180 WW OPAL GR.





#### **PHOTOMETRIC DATA:**


F31SF196MOOP830NG  $\eta$  = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









#### **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# ACCESORIES:

# Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.