FIL35





F31SF196MOOP830NW

- FIL35 SUR 1960 5180 WW OPAL WH.

Description:

Finish: Matte white RAL 9010



Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.989 lm
 %:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 106,8 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 25W

...,

Gear: Electronic

Light output tolerance +/- 10%


EPD

CUSTOM MADE OPTIONS:



FIL35









PHOTOMETRIC DATA:


 $F31SF196MOOP830NW \\ \eta = 100\% \\ Imax = 389 \ cd/klm \\ UTE: \ 1,00E$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.