


F31SF224LOIC840DB

**FIL35 SUR 2240 3200 NW D/I COMF DALI BK.****Description:**

Suspended structure model FIL35 SUR 2240 3200 NW D/I OP COMF DALI BK. LAMP brand. Made of extruded aluminium painted in matt black. Indirect-direct light. With an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, neutral white color temperature and control DALI gear included. With IP20, IK07 protection rating. Insulation class I. Photobiological safety group 0.

Finish: Matte black RAL 9011

Dimensions: 2.240 x 35 x 80 mm

Installation: Suspended
TECHNICAL SPECIFICATIONS:

Light output:	4.574 lm	°K :	4000
Plum:	41,7W	CRI :	80
Efficacy:	108,6 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER TRIDONIC	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	36W		

Light output tolerance +/- 10%
CUSTOM MADE OPTIONS:


ACCESSORIES :

Assembly



Product code:
F3COX/MMB

Description:
FIL 35 ACC. COVER X/MM BK.




Product code:
F3COX/MMG

Description:
FIL 35 ACC. COVER X/MM GR.



Product code:
F3COX/MMW

Description:
FIL 35 ACC. COVER X/MM WH.



Product code:
F3FX50B

Description:
ACC. WALL BRACKET FIL45 50MM BK.




Product code:
F3FX50G

Description:
ACC. WALL BRACKET FIL35 50MM GR.




Product code:
F3FX50W

Description:
ACC. WALL BRACKET FIL35 50MM WH.



Product code:
F3SUECB

Description:
FIL35 ACC. SUR END COVER BK.



Product code:
F3SUECG

Description:
FIL35 ACC. SUR END COVER GR.



Product code:
F3SUECW

Description:
FIL35 ACC. SUR END COVER WH.

ACCESSORIES :

Suspension

FIL35



Product code:

F3SUWIDE1000G

Description:

FIL35 ACC. QUICK STEEL CABLE 1M NK.



Product code:

F3SUWIDE4000G

Description:

FIL35 ACC. QUICK STEEL CABLE 4M NK.

ACCESORIES :
Support



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.