

F31SF224LOOC830DW

**FIL35 SUR 2240 3200 WW OP COMF DALI WH.****Description:**

Suspended or mounted structure model FIL35 SUR 2240 3200 WW OP COMF DALI WH. LAMP brand. Made of extruded aluminium painted in matt black with and opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, warm white color temperature and control DALI gear included. With IP20, IK07 protection rating. Insulation class I. Photobiological safety group 0.

Finish: Matte white RAL 9010**Dimensions:** 2.240 x 35 x 80 mm**Weight:** 4.900 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:****Light output:** 2.224 lm**Plum:** 21,7W**Efficacy:** 102,5 lm/w**UGR:** 19**Type:** MID POWER TRIDONIC**LED Lifetime:** 50.000 L90 B10 (Ta=25°C)**Power:** 22W**°K :** 3000**CRI :** 80**MacAdam:** 3**Power Supply:** 220-240V 50/60Hz**Gear:** Adjustable DALI**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

ACCESORIES :
Assembly**Product code:**

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

**Product code:**

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.

**Product code:**

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.

**Product code:**

F3SUECB

Description:

FIL35 ACC. SUR END COVER BK.

**Product code:**

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.

**Product code:**

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

ACCESORIES :
Suspension**Product code:**

F3SUWIDE1000G

Description:

FIL35 ACC. QUICK STEEL CABLE 1M NK.

**Product code:**

F3SUWIDE4000G

Description:

FIL35 ACC. QUICK STEEL CABLE 4M NK.