


F31SF224LOOC840DB




FIL35 SUR 2240 3200 NW OP COMF DALI BK.

Description:**Finish:** Matte black RAL 9011**Dimensions:** 2.240 x 35 x 80 mm**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	2.224 lm	°K :	4000
Plum:	21,7W	CRI :	80
Efficacy:	102,5 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER TRIDONIC	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	22W		


*Light output tolerance +/- 10%***CUSTOM MADE OPTIONS:**

ACCESORIES :**Assembly****Product code:**

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

**Product code:**

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.

**Product code:**

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.

**Product code:**

F3SUECB

Description:

FIL35 ACC. SUR END COVER BK.

**Product code:**

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.

**Product code:**

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

ACCESORIES :**Suspension****Product code:**

F3SUWIDE1000G

Description:

FIL35 ACC. QUICK STEEL CABLE 1M NK.

**Product code:**

F3SUWIDE4000G

Description:

FIL35 ACC. QUICK STEEL CABLE 4M NK.