


F31SF224LOOC840DG



FIL35 SUR 2240 3200 NW OP COMF DALI GR.

**Description:****Finish:** Gloss grey**Dimensions:** 2.240 x 35 x 80 mm**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	2.224 lm	<b>°K :</b>	4000
<b>Plum:</b>	21,7W	<b>CRI :</b>	80
<b>Efficacy:</b>	102,5 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	MID POWER TRIDONIC	<b>Gear:</b>	Adjustable DALI
<b>LED Lifetime:</b>	50.000 L90 B10 (Ta=25°C)		
<b>Power:</b>	22W		

*Light output tolerance +/- 10%***CUSTOM MADE OPTIONS:**

---

**ACCESORIES :**
**Assembly****Product code:**

F3COX/MMB

**Description:**

FIL 35 ACC. COVER X/MM BK.

**Product code:**

F3COX/MMG

**Description:**

FIL 35 ACC. COVER X/MM GR.

**Product code:**

F3COX/MMW

**Description:**

FIL 35 ACC. COVER X/MM WH.

**Product code:**

F3SUECB

**Description:**

FIL35 ACC. SUR END COVER BK.

**Product code:**

F3SUECG

**Description:**

FIL35 ACC. SUR END COVER GR.

**Product code:**

F3SUECW

**Description:**

FIL35 ACC. SUR END COVER WH.

---

**ACCESORIES :**
**Suspension****Product code:**

F3SUWIDE1000G

**Description:**

FIL35 ACC. QUICK STEEL CABLE 1M NK.

**Product code:**

F3SUWIDE4000G

**Description:**

FIL35 ACC. QUICK STEEL CABLE 4M NK.