Product datasheet

FIL35



F31SF224MOOP830NG



- FIL35 SUR 2240 5920 WW OPAL GR.

Description:

Finish: Gloss grey

80

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 3.416 lm
 %:
 3000

 Plum:
 32,5W
 CRI:
 80

 Efficacy:
 96,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 30,2W

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL35




FIL35 SUR 2240 5920 WW OPAL GR.





PHOTOMETRIC DATA:


F31SF224MOOP830NG η = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.