### **Product datasheet**

### FIL35



#### F31SF224MOOP840NG



### - FIL35 SUR 2240 5920 NW OPAL GR.

#### Description:

Finish: Gloss grey



#### Installation: Surface

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 3.544 lm
 % :
 4000

 Plum:
 32,5W
 CRI :
 80

 Efficacy:
 96,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 30,2W

Light output tolerance +/- 10%



## **CUSTOM MADE OPTIONS:**



### FIL35



FIL35 SUR 2240 5920 NW OPAL GR.





#### **PHOTOMETRIC DATA:**


F31SF224MOOP840NG  $\eta$  = 100% lmax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









#### **Product datasheet**

### FIL35



## ACCESORIES:

## Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code: F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# ACCESORIES:

## Support



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.