


F31TR112LOOC830DW




FIL35 TRIM 1120 1600 WW OP COMF DALI WH.

Description:


Structure to recessed model FIL35 TRIM 1120 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with and opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring Dali included. With IP43, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED lifetime: 50.000 L90 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Dimensions:** 1.120 x 51 x 76 mm**Weight:** 3.000 g**Installation:** Recessed**Recessing measures:** 1,127 x 52 x 0 mm**TECHNICAL SPECIFICATIONS:**

Light output:	1.068 lm	°K :	3000
Plum:	12,1W	CRI :	80
Efficacy:	88,2 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	11W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :



ACCESORIES :

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.




Product code:

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.




Product code:

F3PRTRX/MMW

Description:

FIL 35 ACC. TRIMLESS PROFIL X/MM WH.



Product code:

F3REJO

Description:

FIL35 ACC. INTM JOINT B RECESSED



Product code:

F3TRECW

Description:

FIL35 ACC. TRIM END COVER WH.

ACCESORIES :

Optical



Product code:

F3DIX/MMOP

Description:

FIL 35 ACC. OPAL DIFFUSER X/MM