


F31TR196MOOP830NW




FIL35 TRIM 1960 5180 WW OPAL WH.

Description:


Structure to recessed model FIL35 TRIM 1960 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring included. With IP43, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED lifetime: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Dimensions:** 1.960 x 51 x 76 mm**Weight:** 4.650 g**Installation:** Recessed**Recessing measures:** 1,967 x 52 x 0 mm**TECHNICAL SPECIFICATIONS:**

Light output:	2.989 lm	°K :	3000
Plum:	28W	CRI :	80
Efficacy:	106,8 lm/w	MacAdam:	3
Type:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	25W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :



ACCESSORIES :
Assembly**Product code:**

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

**Product code:**

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.

**Product code:**

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.

**Product code:**


F3JO

F3REJO

Description:

FIL35 ACC. INTM JOINT B

FIL35 ACC. INTM JOINT B RECESSED

**Product code:**

F3PRTRX/MMW

Description:

FIL 35 ACC. TRIMLESS PROFIL X/MM WH.

**Product code:**

F3SUECB

Description:

FIL35 ACC. SUR END COVER BK.

**Product code:**

F3SUECG

Description:

FIL35 ACC. SUR END COVER GR.

**Product code:**

F3SUECW

Description:

FIL35 ACC. SUR END COVER WH.

**Product code:**


F3TRECW

Description:

FIL35 ACC. TRIM END COVER WH.

ACCESSORIES :
Optical

FIL35



Product code:
F3DIX/MMOP

Description:
FIL 35 ACC. OPAL DIFFUSER X/MM