#### Product datasheet

FIL45

## F41RE224MOOP830DG



#### FIL45 REC 2240 5200 WW OPAL DALI GR.

#### **Description:**

Structure to recessed model FIL45 REC 2240 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring Dali included. With IP43, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish:Gloss greyDimensions:2.240 x 55 x 76 mm

Weight: 5.160 g

Installation: Recessed

Recessing measures: 2,246 x 51 x 0 mm

#### **TECHNICAL SPECIFICATIONS:**

Light output:	3.444 lm	٩K :	3000		
Plum:	37W	CRI :	80		
Efficacy:	93 lm/w	MacAdam:	<b>lam:</b> 3		
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	70.000 L80 B10 (Ta=25ºC)	Gear:	Adjustable DALI		
Power:	31W				

#### Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

# FIL45

F41RE224MOOP830DG

FIL45 REC 2240 5200 WW OPAL DALI GR.



F41RE224MOOP830NG	180°	alpha = 104,6°	H (m)	D (m)	Emax	Emed
η = 100%			1	2,59	1259	433
Imax = 380 cd/klm						
UTE: 1,00E	90° 90°		2	5,18	315	108
CIE: 49 81 97 100 100			3	7 77	140	10
			3	7,77	140	48
	0°		4	10,35	79	27

Worktitude for light

### **Product datasheet**

# FIL45

## ACCESORIES :

## Assembly




Product code: F42JO

**Description:** FIL45 ACC. SU/RE INTM JOINT B



Product code: F4COX/MMB



Worktitude for light



Product code: Description: F4COX/MMG FIL 45 ACC. COVER X/MM GR.



Product code: F4PRREX/MMB



FIL 45 ACC. REC PROFIL X/MM BK.



Product code: F4COX/MMW

Description: FIL 45 ACC. COVER X/MM WH.



Product code: F4PRREX/MMG

Description: FIL 45 ACC. REC PROFIL X/MM GR.





Description: FIL 45 ACC. REC PROFIL X/MM WH.



Product code: F4REECB

Description: FIL45 ACC. REC END COVER BK.



Product code: F4REECG

Description: FIL45 ACC. REC END COVER GR.



Product code: F4REECW

Description: FIL45 ACC. REC END COVER WH.

### Product datasheet

# FIL45





Product code: F4TORFG Description: FIL45 ACC. TOOL REMOVE REFLECTOR

# ACCESORIES : Optical



Product code: F4DIX/MMOP Description: FIL 45 ACC. OPAL DIFFUSER X/MM

# ACCESORIES : Adjustment and control



Product code: F41EMG3HDWB





Product code: F41EMG3HDWG

Description: ACC.FIL45 DOWNLIGHT EMERGENCIA 3H GR



Product code: F41EMG3HDWW

Description: ACC.FIL45 DOWNLIGHT EMERGENCIA 3H WH



Product code: F41LIGHTSNDB

Description: ACC.FIL45 SENSOR BASIC ILD DALI-2 BK



Product code: F41LIGHTSNDG





Product code: F41LIGHTSNDW

Description: ACC.FIL45 SENSOR BASIC ILD DALI-2 WH