FIL45

F41SF168HOOP830DG FIL45 SUR 1680 9300 WW OPAL DALI GR.



Description:

Suspended or mounted surface structure model FIL45 SUR 1680 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring Dali included. With IP43, except for suspended installation, which becomes IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available, white, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Gloss grey

Dimensions: 1.680 x 45 x 80 mm Weight: 3.550 g

Installation: Surface



TECHNICAL SPECIFICATIONS:

Light output: 5.592 lm °K: 3000 Plum: 58,7W CRI: 80 Efficacy: 95,3 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

Power: 54W

Light output tolerance +/- 10%

ΙP LED CLASE 07 43 3000°k























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













FIL45




FIL45 SUR 1680 9300 WW OPAL DALI GR.





PHOTOMETRIC DATA:


F41SF168HOOP830NG η = 100% lmax = 377 cd/klmUTE: 1,00E

CIE: 49 80 96 100 100









FIL45



ACCESORIES:

Assembly



Product code:

F4COX/MMB



FIL 45 ACC. COVER X/MM BK.



Product code:

F4COX/MMG



FIL 45 ACC. COVER X/MM GR.



Product code:

F4COX/MMW



FIL 45 ACC. COVER X/MM WH.



Product code:

F4FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

F4FX50G

Description:

ACC. WALL BRACKET FIL45 50MM GR.



Product code:

F4FX50W

Description:

ACC. WALL BRACKET FIL45 50MM WH.



Product code:

F4PRSUX/MMB

Description:

FIL 45 ACC. SUS PROFIL X/MM BK.



Product code:

F4PRSUX/MMG

Description:

FIL 45 ACC. SUS PROFIL X/MM GR.



Product code:

F4PRSUX/MMW

Description:

FIL 45 ACC. SUS PROFIL X/MM WH.



Product code:

F4SUECB

Description:

FIL45 ACC. SUR END COVER BK.

FIL45





Product code:

F4SUECG



Product code:

F4SUECW



FIL45 ACC. SUR END COVER WH.

ACCESORIES:

Suspension



Product code:

F4SUCAEMFA1000NB F4SUCAEMFA4000NB



ACC. ELECMEC FIL45 QUICK SUSP 1M BK. ACC. ELECMEC FIL45 QUICK SUSP 4M BK.

FIL45 ACC. SUR END COVER GR.



Product code:

F4SUCAEMFA1000NG F4SUCAEMFA4000NG



ACC. ELECMEC FIL45 QUICK SUSP 1M GR. ACC. ELECMEC FIL45 QUICK SUSP 4M GR.



Product code:

F4SUCAEMFA1000NW F4SUCAEMFA4000NW



ACC. ELECMEC FIL45 QUICK SUSP 1M WH. ACC. ELECMEC FIL45 QUICK SUSP 4M WH.



Product code:

F4SUCAWI1000DB F4SUCAWI4000DB



ACC. ELECMEC FIL45 QUICK SUSP 1M 5P BK. ACC. ELECMEC FIL45 QUICK SUSP 4M 5P BK.



Product code:

F4SUCAWI1000DG F4SUCAWI4000DG

Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M 5P GR. ACC. ELECMEC FIL45 QUICK SUSP 4M 5P GR.



Product code:

F4SUCAWI1000DW F4SUCAWI4000DW



Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M 5P WH. ACC. ELECMEC FIL45 QUICK SUSP 4M 5P WH.



Product code:

F4SUWIDE1000G

Description:

FIL45 ACC. QUICK STEEL CABLE 1M NK.



Product code:

F4SUWIDE4000G

Description:

FIL45 ACC. QUICK STEEL CABLE 4M NK.

Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL45



ACCESORIES:

Support



Product code: Description:

F4FX15G FIL45 ACC. CEILING BRACKET 15MM GR.

ACCESORIES:

Optical



Product code: Description:

F4DIX/MMOP FIL 45 ACC. OPAL DIFFUSER X/MM

ACCESORIES:

Adjustment and control



Product code: F41EMG3HDWB Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H BK



Product code: F41EMG3HDWG

Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H GR

Product code: F41EMG3HDWW

Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H WH

Product code:

F41LIGHTSNDB

Description:

ACC.FIL45 SENSOR BASIC ILD DALI-2 BK

Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL45





Product code: F41LIGHTSNDG

Description:

ACC.FIL45 SENSOR BASIC ILD DALI-2 GR



Product code:

F41LIGHTSNDW

Description:

ACC.FIL45 SENSOR BASIC ILD DALI-2 WH