### FIL45

### F41SFCRMOPR830DB



### FIL45 CORNER SUR 1300 WW OP COMF DALI BK


### Description:

Suspended or mounted surface structure model FIL45 CORNER SUR LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<16. Model for LED MID-POWER, colour temperature 3000K with CRI80 and with electronic wiring Dali included. With IP43, except for suspended installation, which becomes IP20, IK07 protection rating. Insulation class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration -EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

Weight: 1.400 g

Installation: Surface



### **TECHNICAL SPECIFICATIONS:**

Light output: 960 lm °K: 3000 Plum: 10,8W CRI: 80 Efficacy: 88,9 lm/w 3 MacAdam:

UGR: Power Supply: 220-240V 50/60Hz Type: MID POWER LED Gear: Adjustable DALI

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power:

### Light output tolerance +/- 10%































**CUSTOM MADE OPTIONS:** 









Data according to regulations 2019/2020/EU and 2019/2015/EU















# FIL45








# FIL45 CORNER SUR 1300 WW OP COMF DALI BK

### **PHOTOMETRIC DATA:**

 $\begin{array}{l} \text{F41SFCRMOPR830NB} \\ \eta = 99\% \\ \text{Imax} = 968 \text{ cd/klm} \\ \text{UTE: 0,99A} \\ \text{CIE: 90 100 100 100 99} \end{array}$ 







Data according to regulations 2019/2020/EU and 2019/2015/EU

### FIL45



**ACCESORIES:** 

# **Assembly**



Product code:

F42JO



FIL45 ACC. SU/RE INTM JOINT B



Product code:

F4COX/MMB



FIL 45 ACC. COVER X/MM BK.



Product code:

F4COX/MMG

Description:

FIL 45 ACC. COVER X/MM GR.



Product code:

F4COX/MMW

Description:

FIL 45 ACC. COVER X/MM WH.



Product code:

F4PRSUX/MMB

# Description:

FIL 45 ACC. SUS PROFIL X/MM BK.



Product code:

F4PRSUX/MMG



FIL 45 ACC. SUS PROFIL X/MM GR.



Product code:

F4PRSUX/MMW

# Description:

FIL 45 ACC. SUS PROFIL X/MM WH.



Product code:

F4SUECB

Description:

FIL45 ACC. SUR END COVER BK.



Product code:

F4SUECG

Description:

FIL45 ACC. SUR END COVER GR.



Product code:

F4SUECW

Description:

FIL45 ACC. SUR END COVER WH.

# FIL45





Product code:

Description:

F4TORFG FIL45 ACC. TOOL REMOVE REFLECTOR

# ACCESORIES:

### Suspension



Product code:

F4SUCAEMFA1000NB F4SUCAEMFA4000NB

### Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M BK.
ACC. ELECMEC FIL45 QUICK SUSP 4M BK.



Product code:

F4SUCAEMFA1000NG F4SUCAEMFA4000NG

### Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M GR.
ACC. ELECMEC FIL45 QUICK SUSP 4M GR.



Product code:

F4SUCAEMFA1000NW F4SUCAEMFA4000NW

# Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M WH. ACC. ELECMEC FIL45 QUICK SUSP 4M WH.



Product code:

F4SUCAWI1000DB F4SUCAWI4000DB



ACC. ELECMEC FIL45 QUICK SUSP 1M 5P BK.

ACC. ELECMEC FIL45 QUICK SUSP 4M 5P BK.



Product code:

F4SUCAWI1000DG F4SUCAWI4000DG

# Description:

ACC. ELECMEC FIL45 QUICK SUSP 1M 5P GR. ACC. ELECMEC FIL45 QUICK SUSP 4M 5P GR.



Product code:

F4SUCAWI1000DW F4SUCAWI4000DW



ACC. ELECMEC FIL45 QUICK SUSP 1M 5P WH. ACC. ELECMEC FIL45 QUICK SUSP 4M 5P WH.



Product code:

F4SUWIDE1000G

### Description:

FIL45 ACC. QUICK STEEL CABLE 1M NK.



Product code:

F4SUWIDE4000G

### Description:

FIL45 ACC. QUICK STEEL CABLE 4M NK.

Data according to regulations 2019/2020/EU and 2019/2015/EU

# FIL45



ACCESORIES:

Support



Product code: Description:

F4FX15G FIL45 ACC. CEILING BRACKET 15MM GR.

**ACCESORIES:** 

Optical



Product code: Description:

F4DIX/MMOP FIL 45 ACC. OPAL DIFFUSER X/MM